TECHNICAL DATA	STANDARD	SOMPLAN 350
CLASSIFICATION		
Type of Floorcovering	ISO 10581	Homogeneous Compact vinyl floorcovering
Classification	ISO 10874	Classes:
	Commercial	34
	Industrial	43
TECHNICAL CHARACTERISTICS Total thickness	ISO 24346	2.0mm
Total thickness	ISO 24346	2.0mm
Dimension - Length	ISO 24341	23lm
Dimension - Width	ISO 24341	2m
Total weight	ISO 23997	3300g/m²
Surface treatment		PUR
Binder content	ISO 10581	Туре II
TECHNICAL PERFORMANCES		
TECHNICAL PERFORMANCES		
Dimensional stability	ISO 23999	≤ 0.40% (Rolls)

Dimensional stability	ISO 23999	≤ 0.40% (Rolls)
Curl resistance to heat	ISO 23999	≤ 4.00mm
Reaction to fire	EN 13501-1	Bri -s1
Residual indentation	ISO 24343-1 - measured value	0.03mm
	Required value	≤ 0.10mm
Castor chair test	ISO 4918 - EN 425	No damage
Thermal resistance	EN ISO 10456	0.04 (m ² ·K)/W
Light fastness	ISO 105 B02	≥ 6
Chemical resistance	ISO 26987	Good resistance
Slip resistance	DIN 51130	R9
Static electrical charge	EN 13893	μ≥ 0.3
	EN 1815	≤ 2kV
Bacteria resistance	ISO 846-C	Doesn't favour growth
Flexibility	ISO 24344	20 mm – No crack
ENVIRONMENT		
TVOC 28 days AgBB test	ISO 16000	< 10ug/m³

Phthalate-free technology

The above information is subject to modification for the benefit of further improvement.













OTarkett

Somplan 350

HOMOGENEOUS COMPACT VINYL FLOORCOVERING

Somplan 350

The fresh and soft solution for heavy-traffic areas









Somplan 350



Somplan 350 306007026 / 306007001

© 306007 015 © 306007 016 © 306007 017 © 306007 018 © 306007 019 © 306007 021 © 306007 020 © 306007 023 © 306007 024 © 306007 025 © 306007 026 © 306007 022

HIGH QUALITY HOMOGENEOUS VINYL FLOORING

Somplan 350 is a homogeneous vinyl flooring inspired by natural beauty, with fresh and soft feeling and non-directional design. It has proven performance in heavy traffic healthcare settings. It's a low maintenance solution, easy to heat weld and flexible to cove for spaces demanding superior infection.

Key features:

- High resistance to soils, stains, chemicals, scratches, scuffs and abrasionsPhthalate-free and extremely low VOC emissions for the users' health and safety
- *Superior PUR treatment enabling easy maintenance and minimized cleaning time
- •Through pattern construction for the best durability and abrasion resistance
- •Non-directional design available in 24 natural colours

C M Y K

Somplan 350 Size: 495 x 310 mm

@ 306007 011
*Made to order, no samples available.